

AMENDMENTS TO THE CLAIMS

1. (Canceled)

2. (Currently Amended) ~~The method as claimed in claim 1~~ A method for transforming a heterogeneous compound document to a desired format based on a prescribed model comprising the steps of:

(i) specifying components of the heterogeneous compound document as a hierarchical tree structure in multiple formats and specifying input sources of information for each of the components as part of said prescribed model;

(ii) verifying and composing the heterogeneous compound document using a modeling language parser and a document composer by dynamically obtaining input information from the input sources of information specified in said prescribed model; and

(iii) converting the heterogeneous compound document to the desired format using the document composer,

wherein the step of specifying components of heterogeneous compound document as a hierarchical tree structure is carried out by:

(i) identifying hierarchical structure of the heterogeneous compound document and determining the root nodes, internal nodes and leaf nodes;

(ii) creating a leaf element in model description of the heterogeneous compound document for each leaf node and describing each of the leaf node in each of the required formats, with the proviso that for each value in the node, a stream start symbol, a stream descriptor, the value and a stream end symbol are added to list of values corresponding to the given format in the leaf

element, if input is to be obtained from a new source of data, otherwise a constant value which is specified by the leaf node is added to the list of values corresponding to the given format in the leaf element;

(iii) creating an internal node element in the model description of the heterogeneous compound document for each identified internal node and describing each of the internal node in each of the required formats for each child node of the node with the proviso that:

- (a) if the input for the child node is to be obtained from a new source of data, a stream start symbol and a stream descriptor are added to the list of values corresponding to the given format in the internal node element;
- (b) if the child node is leaf node, the corresponding leaf element is added to the list of values corresponding to the given format and a stream end symbol is also added, if a stream start symbol was added in step (a);
- (c) if the child node is an internal node, a reference to the corresponding internal node element is added to the list of values corresponding to the given format and a stream end symbol is also added, provided a stream start symbol was added in step (a);

(iv) creating a root element in the model description of the heterogeneous compound document for each identified root node and describing a each of the root node in each of the required formats for each child node of node with the proviso that:

- (a) if the input to the child node is to be obtained from a new source of data, a stream start symbol and a stream descriptor are added to the list of values corresponding to the given format in the root element,
- (b) if the child node is a leaf node, a reference to the corresponding leaf element is added to the list of values corresponding to the given format in the

root element, and a stream end symbol is also added if a stream start symbol was added in step (a),

- (c) if the child node is an internal node, a reference to the corresponding internal node element of the model is added to the list of values corresponding to the given format of the root element, and a stream end symbol is also added if a stream start symbol was added in step (a).

3. (Currently Amended) ~~The method as claimed in claim 1~~ A method for transforming a heterogeneous compound document to a desired format based on a prescribed model comprising the steps of:

(i) specifying components of the heterogeneous compound document as a hierarchical tree structure in multiple formats and specifying input sources of information for each of the components as part of said prescribed model;

(ii) verifying and composing the heterogeneous compound document using a modeling language parser and a document composer by dynamically obtaining input information from the input sources of information specified in said prescribed model; and

(iii) converting the heterogeneous compound document to the desired format using the document composer,

wherein the step of verifying and composing the heterogeneous compound document is carried out by:

(i) providing a model of the heterogeneous compound document and a document format identifier as inputs;

(ii) parsing the input model using a modeling language parser and updating a model database with the parsed model information;

(iii) obtaining a default input stream for the implementation of the method and pushing the same into a stream stack;

(iv) considering each root element in the parsed model information and obtaining a value list corresponding to the input document format specified by the input document format identifier from the root element;

(v) performing the following steps on the value list obtained in the previous step:

- a) repeating step (v) with next value for a constant value which matches with the input values obtained from the stream on top of the stream stack;
- b) obtaining a value list corresponding to the internal node element or leaf element from the model database and recursively repeating step (v) with a new list for a value which is a reference to an internal node element or a leaf element;
- c) obtaining the next value which will be the stream descriptor for a value which is a stream start symbol and providing the stream descriptor to the stream module to obtain a new stream and pushing it into the stream stack;
- d) popping the top most stream from the stream stack and using the current top most stream for further processing for a value which is a stream end symbol;

(vi) popping all the streams from the stream stack except for the default input stream, resetting the default input stream and repeating step (iv) onwards with the next root element in the model, till all values in the value list match with the input and the root element contains the heterogeneous compound document information.

4-5. (Canceled)